

GIS Tools for Environmental Assessment to meet Renewable Energy Goals

Amjad A Abu Sirhan

Al Balqa Applied University

Introduction

- The identification of areas technically suitable for renewable generation involves :
- Collection of needed data, such as historical wind speed and direction, terrain and slope information, and solar radiation.
- Data must be analyzed by GIS tools to get information.

Data collection

The needed data include:

Data from metrological stations: Collected as numbers

Wind speed and duration reading

Sun intensity and number of sunny days

Data from satellite images

Land Use\Cover

Urban Areas

Protected Areas

Roads

Slope of land




Data Analysis

- From collected data, the technical sites for renewable energy production can be selected:
- Suitability based on weather reading.
- Distance from Road
- Distance from urban.
- Slope of land.

Data from metrological stations is collected as numbers



GIS tools used to create maps from weather data




Wind Power Generation

For wind power generation: wind speed and duration must be sufficient for turbines to work.

Data from metrological stations (wind speed and duration) is used to create the wind map.

Wind suitability map: Created from wind speed and wind duration maps




Solar Power generation

For solar power generation : Sun intensity and the number of sunny days dictate the suitability of an area.


Means of sun intensity readings

Means of sun duration readings

Solar Map: Created from sun intensity map and number of sunny days



Limitations of areas technically suitable for renewable energy



Evaluation according to cost and slope


- Areas that are suitable to renewable energy based on weather data are classified to:
 - Highly suitable
 - Moderately suitable
 - Marginally suitable

According to land use\cover: protected areas
road network, urban areas, and slope of land


Source of data: Satellite Image: urban,
Road, Slope




Land use/cover




Urban Areas



Slope Limitations



GIS overlay process is used to create final land suitability map



Final Land suitability map for wind power generation

Wind Power Exclusion Map

The application of this filter allows estimating the available area around **16 %** of the total surface of Jordan. Taking into account these figures, the wind technical potential is **3.6 GW**.

